



## **DECLARATION OF PERFORMANCE**

Nο

1343-CPR-M 545-17 EN

EN

1. Unique identification code of the

product-type:

**PV 45-PRO** 

2. Intended use/es:

Bonded injection type anchor for use in non-cracked concrete.

Product area code: 33

3. Manufacturer: DEWALT / Powers

Richard-Klinger-Str. 11 65510 Idstein Germany

4. Authorised representative: **not applicable** 

5. System/s of AVCP: System 1

6. European Assessment Document:

European Technical Assessment:

Technical Assessment Body:

Notified body/ies:

ETAG 001-Part 1 and Part 5, Edition 2013 used as EAD

ETA-13/0061 (28.06.2016)

TZÚS - TECHNICKÝ A ZKUŠEBNÍ ÚSTAV STAVEBNÍ Prague

**NB 1343 MPA Darmstadt** 

7. Declared performance/s:

Mechanical resistance and stability (BWR 1)

<b>Essential Characteristics</b>	Performance
Characteristic resistance for tension loads	See Annex C1
Characteristic resistance for shear loads	See Annex C 2
Displacement	See Annex C 3

Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Anchorages satisfy requirements for
	Class A1
Resistance to fire	No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Karl Evans
Vice President

Professional Power Tools EANZ

Idstein, 10.07.2018

CETAL C

**Dr.-Ing. Philipp Mahrenholtz**Senior Engineering Manager

This DoP has been prepared in different languages. In case there is a dispute on the interpretation the English version shall always prevail.

DoP No. 1343-CPR-M 545-17 (R6)